

ITEM NO.	1	2	3	4	5	6	7	8	9	10
Number of Plies	2	3	2	2	2	2	3	3	4	4
Working Strength Rating per inch of width(lbs)	150	225	150	150	220	220	330	330	440	440
Top cover(inch)	BARE	BARE	1/32	1/32	1/8	3/16	3/16	1/4	1/4	3/8
bottom cover(inch)	BARE	BARE	1/32	1/32	1/16	1/16	1/16	1/16	1/16	3/32
Thickness(mm)	2.8	3.6	3.9	4.2	7.5	9.0	10.0	11.6	13.2	17.2
Color			Black	Black	Black	Black	Black	Black	Black	Black
Rubber grade	RMA II	RMA II	RMA II	RMA II	RMA I & II	RMA I & II	RMA I & II	RMA I & II	RMA I & II	RMA I & II
Available widths	Max. 72"	Max. 72"	Max. 72"	Max. 72"	Max. 72"	Max. 72"	Max. 72"	Max. 72"	Max. 72"	Max. 72"

***Other specification are also available and made to order , please contact our sales office.

ITEM NO.	11	12	13	14	15	16	17	18	19	20
Number of Plies	2	3	3	2	3	2	2	3	3	3
Working Strength Rating per inch of width	220	330	330	220	330	150	150	225	225	225
Top cover	3/16	3/16	1/4	3/16	3/16	R.T	R.T	R.T	R.T	R.T
bottom cover	1/16	1/16	1/16	1/16	1/16	BARE	BARE	BARE	BARE	BARE
Thickness(mm)	9.0	10.0	11.6	9.2	10.5	6.4	6.4	7.2	7.2	7.2
color	Black	Black	Black	Black	Black	BLK	TAN	BLK	TAN	PURE GUM
Rubber grade	400°F EPDM	400°F EPDM	400°F EPDM	300°F HOT	300°F HOT					
Available widths	Max. 72"	Max. 72"	Max. 72"	Max. 72"	Max. 72"	60" &48"	60" &48"	60" &48"	60" &48"	60" &48"

***Other specification are also available and made to order , please contact our sales office.

ITEM NO.	21	22	23	24	25
Number of Plies	2	3	3	2	3
Working Strength Rating per inch of width	220	330	330	220	330
Top cover	1/8 V6 Cleat	1/8 V6 Cleat	1/8 V6 Cleat	1/8 CHEVRON	3/16 CHEVRON
bottom cover	1/16	1/16	bare	1/16	1/16
Thickness(mm)	12.7	13.7	12.7		
color	BLK	BLK	BLK	BLK	BLK
Rubber grade	MOR	MOR	MOR	MOR	MOR
Available widths	60"	60"	60"	40" BELOW	40" BELOW

***Other specification are also available and made to order , please contact our sales office.