

HSING KWO RUBBER MFG. CO., LTD

Regular Specification List of Multi-Ply Conveyor Belt

| ITEM NO. | 1 | 2 | 3 | 4 | 5 | 6 | 7 | 8 | 9 | 10 | 11 | 12 |
|-------------------------------|--------------------|--------------------|--------------------|------------|------------|------------|---------------|---------------|---------------|--------------|--------------------|--------------------|
| Number of Plies | 2 | 3 | 2 | 2 | 2 | 2 | 3 | 3 | 4 | 4 | 2 | 3 |
| Tension Rating (PIW) | 150 | 225 | 150 | 150 | 220 | 220 | 330 | 330 | 440 | 440 | 220 | 330 |
| Top Cover Thickness (inch) | BARE | BARE | 1/32" | 1/32" | 1/8" | 3/16" | 3/16" | 1/4" | 1/4" | 3/8" | 3/16" | 3/16" |
| Bottom Cover Thickness (inch) | BARE | BARE | BARE | 1/32" | 1/16" | 1/16" | 1/16" | 1/16" | 1/16" | 3/32" | 1/16" | 1/16" |
| Overall Gauge (mm) | 2.8 | 3.6 | 3.9 | 4.2 | 7.5 | 9.0 | 10.2 | 11.8 | 13.4 | 17.2 | 9.0 | 10.2 |
| Color | - | - | Black | Black | Black | Black | Black | Black | Black | Black | Black | Black |
| Rubber Grade | RMA II | RMA II | RMA II | RMA II | RMA I & II | RMA I & II | RMA I & II | RMA I & II | RMA I & II | RMA I & II | 400 ^o F | 400 ^o F |
| Available Widths (inch) | Max. 80" | Max. 80" | Max. 80" | Max. 80" | Max. 80" | Max. 80" | Max. 80" | Max. 80" | Max. 80" | Max. 80" | Max. 80" | Max. 80" |
| ITEM NO. | 13 | 14 | 15 | 16 | 17 | 18 | 19 | 20 | 21 | 22 | 23 | |
| Number of Plies | 3 | 2 | 3 | 2 | 3 | 3 | 2 | 3 | 3 | 2 | 3 | |
| Tension Rating (PIW) | 330 | 220 | 330 | 150 | 225 | 225 | 220 | 330 | 330 | 220 | 330 | |
| Top Cover Thickness (inch) | 1/4" | 3/16" | 3/16" | R.T. | R.T. | R.T. | 1/8" V6 Cleat | 1/8" V6 Cleat | 1/8" V6 Cleat | 1/8" Chevron | 3/16" Chevron | |
| Bottom Cover Thickness (inch) | 1/16" | 1/16" | 1/16" | BARE | BARE | BARE | 1/16" | 1/16" | BARE | 1/16" | 1/16" | |
| Overall Gauge (mm) | 11.8 | 9.0 | 10.2 | 6.7 | 7.5 | 7.5 | 12.1 | 13.7 | 12.1 | - | - | |
| Color | Black | Black | Black | Black, Tan | Black, Tan | Pure Gum | Black | Black | Black | Black | Black | |
| Rubber Grade | 400 ^o F | 300 ^o F | 300 ^o F | - | - | - | MOR | MOR | MOR | MOR | MOR | |
| Available Widths (inch) | Max. 80" | Max. 80" | Max. 80" | 48" & 60" | 48" & 60" | 48" & 60" | 60" | 60" | 60" | 40" Below | 40" Below | |

* Other specifications are also available, please contact our sales office for further information.